

Bearing No.	Boundary dimensions (mm)					Weight (kg)	Limiting Speed (rpm)	Basic load ratings dyn. Stat. Cr COr (KN)	Effective load ratings dyn. stat. Cw C <sup>ow</sup> (KN)	Limiting radial loads F <sub>r perm</sub> F <sub>or perm</sub> (KN)
	d	B	D	L	r <sub>min</sub>					
LR201 RR	12	10.0	35	15.0	0.6	0.07	15000	6.8/3.05	5.6/2.7	4.5/5.4
LR202 RR	15	11.0	40	14.4	0.6	0.08	14000	7.6/3.7	6.5/3.3	6.6/6.6
LR203 RR	17	12.0	47	18.3	0.6	0.11	11000	9.6/4.75	8.4/4.4	8.8/8.8
LR204 RR	20	14.0	52	17.7	1.0	0.16	10000	12.8/6.6	10.5/5.6	10.7/11.2
LR205 RR	25	15.0	62	21.0	1.0	0.26	9000	14.0/7.8	12.5/7.1	14.2/14.2
LR206 RR	30	16.0	72	24.0	1.0	0.37	7100	19.5/11.3	16.6/9.6	19.2/19.2
LR207 RR	35	17.0	80	25.0	1.1	0.48	6600	25.5/15.3	20.2/11.9	19.5/23.8
LR208 RR	40	18.0	85	27.0	1.1	0.53	5000	22.8/19.8	22.8/13.6	13.4/23.1
LR201 RRU	12	10.0	35	15.0	0.6	0.07	15000	6.8/3.05	5.6/2.7	4.5/5.4
LR202 RRU	15	11.0	40	14.4	0.6	0.08	14000	7.6/3.7	6.5/3.3	6.6/6.6
LR203 RRU	17	12.0	47	18.3	0.6	0.11	11000	9.6/4.75	8.4/4.4	8.8/8.8
LR204 RRU	20	14.0	52	17.7	1.0	0.16	10000	12.8/6.6	10.5/5.6	10.7/11.2
LR205 RRU	25	15.0	62	21.0	1.0	0.26	9000	14.0/7.8	12.5/7.1	14.2/14.2
LR206 RRU	30	16.0	72	24.0	1.0	0.37	7100	19.5/11.3	16.6/9.6	19.2/19.2
LR207 RRU	35	17.0	80	25.0	1.1	0.48	6600	25.5/15.3	20.2/11.9	19.5/23.8
LR208 RRU	40	18.0	85	27.0	1.1	0.53	5000	22.8/19.8	22.8/13.6	13.4/23.1